## **Product specification**



Article-No.: LA-1630

### Holder for steps and walking gratings to mount on trapezoidal and shoulder sheet roofing

Version:

Illustration:

**Aluminum** Applicable for roof pitches till 30 degrees,

custom made after client's requests.

Material: AlMgSi 3 mm.

#### **Description:**

Holder for steps and walking gratings on trapezoidal or shoulder sheet roofs – applicable for roof pitches till 30 degrees.

#### Contents each holder:

1 pce. Angle part, curved according to the requested roof pitch, maximum 30 degrees. With sealing tape on the bottom.

Self-drilling screws A2 – size: 5,5 x 25 mm including sealing disc.

Packing unit: No

Note: If mounted on aluminium-trapezoidal profiles with a thickness under 0.7 mm, you have to fix the holder with rivets!



REES – Holder for steps and walking gratings to mount on trapezoidal roofings. Assemble clamp holder on the raised bead with the self-drilling screws. Suitable for roof pitches of maximum 30 degrees. The clamp holder will be manufactured after the client's requests

Phone: +49 8322-94067-0

Fax: +49 8322-94067-99

Also available for broader gratings. We are looking forward to hearing from you!

A distance of 70 cm between each holder should not be exceeded!

For the correspondingly stable substructure must be provided by the customer.

## **Product specification**



# Holder for steps and walking gratings to mount on trapezoidal and shoulder sheet roofing

#### Mounting:

To assemble clamp holders,	The clamp holder will be	Attention!	The steps and walking
the trapezoidal and	assembled on the raised-	Please do not	gratings will be fixed on the
sandwich-modules have to	bead of the roofing, by the	over tighten the	clamp holders with screws
have a load-bearing capacity,	included self-drilling screws.	self-drilling screws!	and clasps. For fixation use
to stand the additional			the oblong holes.
weight.	Maximum Distance of each		
	holder: 70 cm resp. 27.56		Only use gratings with
Please make sure, that the	inches.		clearance by EN 516-1!
sub construction is stable,			-
according to the required			
conditions and load.			

Note: These holders have no approval according to EN 516-1.

Not suitable for any kind of security-harness or safeguard equipment!

If you have any further questions, please feel free to contact us.

Please note our large product range around metal roofs: snow retention systems, step brackets, solar holders and our program about clips. Further information you will find on our homepage.

Phone: +49 8322-94067-0

Fax: +49 8322-94067-99